

Live Trac EZ [Hardwired Unit]

Spec Sheet

- Live Vehicle Tracker
- Installs in Seconds
- Easily Transfer From Vehicle To Vehicle



LIVE TRAC EZ

Live Trac EZ Tracking Screens



Alert Zone View



Live Chat Support View



Historical Playback View



Dimensions	1.8"W x 2.18"L x 1.08"H	www.LiveViewGPS.com
Operating Temperature	-30° C to +75° C (-22F to +158F)	
Power Source	9 - 16 Volts DC	
Typical full-power current	70mA at 12 Volts DC	
GSM Channels	850/1900 (United States) 900/1800 (Europe, Australia, Asia, & Middle East)	
Communication Protocol	SMS, GPRS (UDP)	
Update Frequency	1-second, 5-second, or 10-second position updates (truly LIVE tracking!)	
OBDII Data	Fuel level , Instantaneous MPG	
Housing	Rugged textured plastic enclosure, V fire rated	
Notifications	20 + reports available	
Historical Playback	90 days of historical playback stored at server	
Reporting	Individual Vehicle Report, Enhanced Vehicle Report, Start/Stop Report, and more...	
Diagnostics	Diagnostics via SMS or TCP diagnostic messages	
Applications	Ranges from everyday tracking to complete fleet solutions	
Shock and Vibration	In accordance with SAEJ1455	