

SX-1 Worldwide GPS Satellite Tracker

[Portable/Battery Powered]

Spec Sheet

- All Satellite Device
- Near Worldwide Coverage
- Rugged & Waterproof
- 7 Year Battery Life With 1 Locate Per Day



SX-1

Product Specifications

PHYSICAL Dimensions Weight	<ul style="list-style-type: none"> 7.25" x 3.25" x 1" (184 x 83 x 25mm) 13 ounces (369g)
APPROVALS Radiated Emissions ESD Compliance Safety Approval Ordnance	<ul style="list-style-type: none"> FCC Part 15 and Part 25, Industry Canada, COFETEL, ETSI EN 301 489-1, and ETSI EN 301 489-3 (CE Mark) EN61000-4-2 U.S. UL913, Class 1, Division 1 (Groups A, B, C, D) INTRINSIC SAFE OPERATION
ENVIRONMENTAL Temperature Humidity Vibration & Shock Type	<ul style="list-style-type: none"> -40 C (-40 F) to +85 C (+185 F) Operating 100% at 50 C, Salt, Fog Testing per MIL STD 810 Testing per MIL STD 810, SAE J1455, and EIC 60521 Exceeds IP68 and NEMA 6P
TRANSMITTER Frequency Protocol Modulation Maximum Tx Time Antenna Packet Size	<ul style="list-style-type: none"> 1.615 GHz Simplex Direct Sequence Spread Spectrum (DSSS) 1.4 Seconds/9 bytes Satellite-GPS 9 Bytes
UNIT OTA IDENTIFICATION Electronic Serial Number	<ul style="list-style-type: none"> Each unit uniquely serialized
DIGITAL COMMUNICATIONS Programming Interface	<ul style="list-style-type: none"> USB HID Device
SENSOR INFORMATION Motion Sensor Interface Integrated	<ul style="list-style-type: none"> Internal USB HID Device Dry Contact
POWER Battery Life Replacement Line Power Capable	<ul style="list-style-type: none"> Lithium Metal Pack fully encased in ultrasonically welded plastic - Primary, 3200mAh up to 4000 Messages Field replaceable without device removal from asset Standard, via USB Interface
MOUNTING OPTIONS ACCESSORY TYPES	<ul style="list-style-type: none"> Tape, Mounting Sled, Screw Programming Tools and Cables, Mounting Accessories, Sensor Cables, Line Cables

www.LiveViewGPS.com